

Bild

Kenngrößen



Kenngrößen	GAFR200 -06	GAFR200 -08	GAFR300 -08	GAFR300 -10	GAFR400 -08	GAFR400 -10	GAFR400 -15	GAFR600 -20	GAFR600 -25
Medium	Druckluft								
Anschluss	1/8"	1/4"	1/4"	3/8"	1/4"	3/8"	1/2"	3/4"	1"
Porenweite im Filter	40µ oder 5µ								
Druckbereich	1,5 - 9 bar								
Prüfdruck	15 bar								
Temperatur	-5 bis +70°C								
Behältervolumen	25 cm <sup>3</sup>		60 cm <sup>3</sup>			100 cm <sup>3</sup>		205 cm <sup>3</sup>	
Gewicht	0,29 kg		0,50 kg			0,88 kg		1,88 kg	

auf Anfrage: max. Druckbereich 4 bar

Bestellbeispiel

	GAFR200	-08	-N	-A	-W	-K
Anschluss	06: 1/8"	08: 1/4"	10: 3/8"	15: 1/2"	20: 3/4"	25: 1"
Behälter	leer: Polycarbonat	C: Metall	N: Nylon	GAFR600 nur mit Metallbehälter		
Entleerung	leer: halbautomatisch	A: automatisch				
Porenweite	Leer: 40 µ	W: 5 µ				
leer: ohne Rückschlagventil	K: mit Rückschlagventil					

Typ	A	AB	AC	B	BA	BC	C	D	K	KA	KB	KC	P	PA	Q
GAFR200-06	52,5	55	31	69	30	39	192,5	M33x1,5	5,4	34	15,4	52	1/8"	120	M5x0,8
GAFR200-08	52,5	55	31	69	30	39	192,5	M33x1,5	5,4	34	15,4	52	1/4"	120	M5x0,8
GAFR300-08	62,5	53	38	82,5	41	41,5	247	M40x1,5	6,5	40	8	52,5	1/4"	158	1/4"
GAFR300-10	62,5	53	38	82,5	41	41,5	247	M40x1,5	6,5	40	8	52,5	3/8"	158	1/4"
GAFR400-08	80	72	52	99	50	49	285,5	M55x2	8,5	55	11	57	1/4"	177,5	1/4"
GAFR400-10	80	72	52	99	50	49	285,5	M55x2	8,5	55	11	57	3/8"	177,5	1/4"
GAFR400-15	80	72	52	99	50	49	285,5	M55x2	8,5	55	11	57	1/2"	177,5	1/4"
GAFR600-20	100	90	59	128	70	58	336,5	M62x1,5	11	66	13	76	3/4"	205	1/4"
GAFR600-25	100	90	59	128	70	58	336,5	M62x1,5	11	66	13	76	1"	205	1/4"

